

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

LM 40 Multifunktionsspray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|--|
| Asp. Tox. | 1 | H304-May be fatal if swallowed and enters airways. |
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Aerosol | 1 | H229-Pressurised container: May burst if heated. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionspray



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

White mineral oil (Natural oil)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

| | |
|--|-----------------------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | |
| Registration number (REACH) | 01-2119457273-39-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 918-481-9 |
| CAS | (64742-48-9) |
| content % | 50-70 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |
| White mineral oil (Natural oil) | |
| Registration number (REACH) | 01-2119487078-27-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 232-455-8 |
| CAS | 8042-47-5 |
| content % | 30-50 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Asp. Tox. 1, H304 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.
Rinse the mouth thoroughly with water.
Do not induce vomiting - give copious water to drink. Consult doctor immediately.
In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

With long-term contact:

drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Chemical pneumonitis (condition similar to pneumonia)

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of sulphur

Oxides of nitrogen

Toxic gases

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.04.2021 / 0003
Replacing version dated / version: 06.03.2020 / 0002
Valid from: 22.04.2021
PDF print date: 14.06.2021
LM 40 Multifunktionsspray

Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid contact with eyes or skin.
If applicable, caution - risk of slipping.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
Without adequate ventilation, formation of explosive mixtures may be possible.
Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Avoid inhalation of the vapours.
Avoid contact with eyes or skin.
Keep away from sources of ignition - Do not smoke.
Take measures against electrostatic charging, if appropriate.
Do not use on hot surfaces.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Observe special regulations for aerosols!
Observe special storage conditions.
Do not store with flammable or self-igniting materials.
Keep protected from direct sunlight and temperatures over 50°C.
Store in a well-ventilated place.
Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionspray

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 800 mg/m³

| Chemical Name | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | Content %:50-70 |
|--------------------------------|--|-----------------|
| WEL-TWA: 800 mg/m ³ | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174) | |
| BMGV: --- | Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40) | |

| Chemical Name | Propane | Content %: |
|---------------------------|--|------------|
| WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: --- | --- |
| Monitoring procedures: | - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990 | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Oil mist, mineral | Content %: |
|---|--------------------------------------|------------|
| WEL-TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH) | WEL-STEL: --- | --- |
| Monitoring procedures: | - Draeger - Oil Mist 1/a (67 33 031) | |
| BMGV: --- | Other information: --- | |

| White mineral oil (Natural oil) | | | | | | |
|---------------------------------|--|-----------------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 92 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 35 | mg/m ³ | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 40 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 160 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, local effects | DNEL | 220 | mg/kg | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 220 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 160 | mg/m ³ | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

Page 6 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,7

Permeation time (penetration time) in minutes:

480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|------------------------------------|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Yellow |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | n.a. |
| Flash point: | Not determined |
| Evaporation rate: | n.a. |
| Flammability (solid, gas): | n.a. |

Page 7 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| | |
|--|---|
| Lower explosive limit: | 0,7 Vol-% |
| Upper explosive limit: | 10,9 Vol-% |
| Vapour pressure: | 4500 hPa (20°C) |
| Vapour density (air = 1): | Not determined |
| Density: | 0,77 g/cm ³ (20°C) |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Mixable |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | No |
| Auto-ignition temperature: | 470 °C (Ignition temperature) |
| Decomposition temperature: | Not determined |
| Viscosity: | Not determined |
| Explosive properties: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising properties: | No |
| 9.2 Other information | |
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | 61,2 % (Organic solvents) |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| LM 40 Multifunktionsspray | | | | | | |
|---|----------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |

Page 8 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| | | | | | | |
|-----------|--|--|--|--|--|--------|
| Symptoms: | | | | | | n.d.a. |
|-----------|--|--|--|--|--|--------|

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | |
|--|----------|-------|-----------------------|------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5000 | mg/m ³ /8h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | | | Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative, Analogous conclusion |
| Carcinogenicity: | | | | | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 414 (Prenatal Developmental Toxicity Study) | Negative, Analogous conclusion |
| Reproductive toxicity: | | | | | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative, Analogous conclusion |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | No indications of such an effect. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | No indications of such an effect., Analogous conclusion |
| Aspiration hazard: | | | | | | Yes |
| Symptoms: | | | | | | unconsciousness, headaches, dizziness |

| White mineral oil (Natural oil) | | | | | | |
|------------------------------------|----------|-------|---------|------------------------|--|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >5 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |

Page 9 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| | | | | | | |
|---|-------|--------|------------|--------|---|----------------------|
| Carcinogenicity: | NOAEL | >1200 | mg/kg | Rat | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |
| Reproductive toxicity: | | | | | OECD 415 (One-Generation Reproduction Toxicity Study) | Negative |
| Reproductive toxicity: | NOAEL | >=1000 | mg/kg bw/d | Rat | OECD 421 (Reproduction/Developmental Toxicity Screening Test) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | >1200 | mg/kg | Rat | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | >1200 | mg/kg | | OECD 452 (Chronic Toxicity Studies) | |
| Aspiration hazard: | | | | | | Asp. Tox. 1 |
| Symptoms: | | | | | | nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | >2000 | mg/kg | Rat | OECD 411 (Subchronic Dermal Toxicity - 90-day Study) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 1000 | mg/kg | Rabbit | OECD 410 (Repeated Dose Dermal Toxicity - 90-Day) | |

| Propane | | | | | | |
|---|----------|--------|---------|------------------------|--|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 260000 | ppmV/4h | Rat | | Gasses, Male, Analogous conclusion |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 21,641 | mg/l | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test) | |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting. |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 7,214 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developmental Tox. Screening Test) | |

Page 10 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| | | | | | |
|---|-------|--------|------|-----|--|
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | LOAEL | 21,641 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) |
|---|-------|--------|------|-----|--|

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| LM 40 Multifunktionsspray | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | | | | | |
|--|----------|------|---------|------|---------------------------------|--|--------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOELR | 28d | 0,1 | mg/l | Oncorhynchus mykiss | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOELR | 21d | 0,18 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | ErL50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOELR | 72h | 1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 80 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | |
| 12.3. Bioaccumulative potential: | Log Pow | | 5,5-7,2 | | | | |
| 12.4. Mobility in soil: | Log Koc | | >3 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.6. Other adverse effects: | | | | | | | Product floats on the water surface. |
| Water solubility: | | | ~10 | mg/l | | | Slight |

| White mineral oil (Natural oil) | | | | | | | |
|---------------------------------|----------|------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |

Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| | | | | | | | |
|--------------------------------------|-----------|-----|-------|------|---------------------------------|--|--------------------------------------|
| 12.2. Persistence and degradability: | | 28d | >60 | % | | OECD 301 B (Ready Biodegradability - Co2 Evolution Test) | Biodegradable |
| 12.6. Other adverse effects: | | | | | | | Product floats on the water surface. |
| 12.1. Toxicity to daphnia: | EL50 | 21d | >1000 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to fish: | LC50 | 96h | >1000 | mg/l | Leuciscus idus | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to fish: | NOEC/NOEL | 96h | >1000 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EL50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | >100 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 48h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | 28d | 31,3 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Not readily biodegradable |
| Toxicity to bacteria: | LC50 | | >1000 | mg/l | activated sludge | | |
| Toxicity to bacteria: | NOELR | | >100 | mg/l | Pseudomonas subspicata | | |

| Propane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,28 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 04 other organic solvents, washing liquids and mother liquors

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Page 12 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number: 1950

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Classification code: 5F

LQ: 1 L

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D



Transport by sea (IMDG-code)

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

EmS: F-D, S-U

Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:

Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Page 13 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 22.04.2021 / 0003
 Replacing version dated / version: 06.03.2020 / 0002
 Valid from: 22.04.2021
 PDF print date: 14.06.2021
 LM 40 Multifunktionsspray

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 61,21 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 15
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Asp. Tox. 1, H304 | Classification according to calculation procedure. |
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard
 Aerosol — Aerosols

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level

Page 14 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 22.04.2021 / 0003
Replacing version dated / version: 06.03.2020 / 0002
Valid from: 22.04.2021
PDF print date: 14.06.2021
LM 40 Multifunktionsspray

DNEL Derived No Effect Level
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.