



tesa® extra Power Universal

BNR 56338, 56348, 56384, 56385, 56386, 56388, 56389, 56396, 56488, 56490

tesa® extra Power Universal is a versatile duct tape with extra bonding power. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

Product Properties

• Applicationfield	Home, Garden, Car, Garage	• Solvent free	yes
• Tear resistant	yes	• Suitable surfaces	Metal, Even wood, Glass, Most plastics, Tiles
• Writable	no	• Reusable	no
• Hand tearable	yes	• Refillable	no
• Spare part service	no	• Waterproof	yes
• UV-resistant	yes	• Recyclable	no
• Water resistant	yes	• Shape	Roll
• Humidity resistant	yes	• Batteries required	no
• Oil- and grease-resistant	yes	• Batteries included	no
• Ozone resistant	yes		

Technical Data

• Application temperature	from 10°C up to 50°C	• Tensile strength	100 N/cm
• Area of use	Outdoor	• Total thickness	215 µm
• Material	PE (polyethylene)	• Temperature resistant	yes
• Ecofriendly packaging	no	• Age-resistant	yes
• Residue-free removable	no	• Temperature resistance	95 °C
• Adhesive strength	High adhesion	up to	
• Type of adhesive	synthetic rubber	• Tensibility	19 %
• Backing material	PE-film with PET-filament	• Hazard material	no

tesa[®] extra Power Universal

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=56338>